



Alpha Series Specifications

Model number	A-715S	A-715SR	A-717S	A-717SR
Model number				
LCD Panel	15" LED backlit display		17" LED backlit display	
MAX.Resolution	1024 x 768 (default)		1280 x 1024 (default)	
Brightness	300 cd/m²			
Touch Screen	Flat Resistive / Projected Capacitive (USB type)			
System Configuration				
CPU	Intel® Celeron® 2.3GHz (fanless) Intel® Core™ i3 3.1GHz (fanless) Intel® Core™ i5 2GHz (fanless) Intel® Core™ i7 2.3GHz (fanless)		Intel® Celeron® 2.3GHz (fanless) Intel® Core™ i3 3.1GHz (fanless) Intel® Core™ i5 2GHz (fanless) Intel® Core™ i7 2.3GHz (fanless)	
Main Memory	204Pin DDR3L RAM x 2 slots, max. 16GB			
Storage	2.5" SATA hard drives or flash storage (SSD), configurable to dual hard drives			
RAID Function	Optional	RAID0/1 (onboard)	Optional	RAID0/1 (onboard)
Remote Management	N/A	Intel AMT9.0 (Core™ i5/i7 CPU required)	N/A	Intel AMT9.0 (Core™ i5/i7 CPU required)
I/O Ports				
Parallel Port	1 x LPT	Optional	1 x LPT	Optional
Serial Ports	4 x DB9 COM 1 x RJ45 COM	5 x RJ45 COM	4 x DB9 COM 1 x RJ45 COM	5 x RJ45 COM
	All with DC 5V/12V powered			
USB Ports	7 x USB2.0			
Powered USB Ports	N/A	2 x 12V P-USB 1 x 24V P-USB	N/A	2 x 12V P-USB 1 x 24V P-USB
LAN Port	1 x Gigabit Ethernet			
Keyboard / Mouse Port	1 x PS/2 keyboard			
Audio Port	1 x Line in, 1 x Line out, 1 x MIC In			
Graphic Port	1 x HDMI			
Cash Drawer Port	1 x RJ12 cash drawer 12V/24V selectable, dual cash drawer support			
Speaker Output	2 x 1W speaker			
DC Output	1 x DC12V out			
Expansion Slot	1 x Mini PCIe slot			
Powering System				
Power Supply	External DC power adapter. AC 100V-240V full range			
Power Button	1 x System on/off button			
LED Indicator	4 x LED indicators (Standby / Power / HDD / LAN Status)			
OSD Control	Full function OSD buttons on display side			
Physical Dimensions				
Dimension (L x W x D)	360 x 360 x 255 mm		11.5Kg	
Weight	10.5Kg			
Safety & Environment				
Product Certification	CE / FCC/CB/LVD certificated			
Operation Temperature	0°C to 40°C			
Storage Temperature	-25°C to 70°C			
O/S Compatibility	Windows 7/ POSReady 7/Windows 8.1 Industry/ Windows 10/ Linux Kernel 3.0 or above			

Alpha Series



15 " Bezel-free, Fanless Touch POS Terminal

Adding flexibility to mission critical needs

- ✓ P-CAP
- ✓ Powered USB
- ✓ OPOS driver
- ✓ RAID 0/1
- ✓ iAMT9.0
- ✓ Win10
- ✓ Cable free



2-in-1 identification reader
MSR, iButton, Fingerprint, RFID

Retail-hardened



Easy access front I/O interface



Easy service hard drives



Retail I/O ports
(A-715SR/717SR)



Fanless design



Water and dust resistant front bezel



Multi-touch PCAP screen

Future proof

The sophisticated design technique and modular engineering provides retailers and restaurateurs the simplest way to build, manage, and grow their business while reducing the total cost of ownership.



Easy service and upgrade system core engine



Interchangeable main touch display (15"/17")



Smart and intuitive cable management



Quad-core

Faster processing power, greater work efficiency.



Sfax : Av.de la liberté Im. El Itkan 3 ème étage Bur. 11 - Sfax 3027
(+216) 74 415 055
Tunis : 7, rue du Lac Côme, Imm. La Brise du Lac, 1er étage, B1 , Les Berges du Lac, 1053, Tunis
(+216) 71 655 261